



SITOP PSU100L/1AC/24VDC/5A

SITOP PSU100L 24 V/5 A Stabilized power supply input: 120/230 V AC, output: 24 V DC/5 A

Input	
Input	1-phase AC
• Note	Set by means of selector switch on the device
supply voltage	
• 1 at AC rated value	120 V
• 2 at AC rated value	230 V
input voltage	
• 1 at AC	93 ... 132 V
• 2 at AC	187 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering	at $V_{in} = 93/187$ V
Mains buffering at $I_{out}$ rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 120 V	2.1 A
• at rated input voltage 230 V	1.15 A
Switch-on current limiting (+25 °C), max.	32 A
duration of inrush current limiting at 25 °C	
• typical	3 ms
$I^2t$ , max.	0.8 A <sup>2</sup> ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic C
Output	
Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	24 V
• output voltage at output 1 at DC rated value	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	150 mV
Adjustment range	22.8 ... 26.4 V

product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
On/off behavior	Overshoot of Vout approx. 4 %
Startup delay, max.	1.5 s
Voltage rise, typ.	130 ms
Rated current value Iout rated	5 A
Current range	0 ... 5 A
• Note	+45 ... +60 °C: Derating 2%/K
supplied active power typical	120 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
<b>Efficiency</b>	
Efficiency at Vout rated, Iout rated, approx.	86 %
Power loss at Vout rated, Iout rated, approx.	17 W
<b>Closed-loop control</b>	
Dynamic mains compensation (Vin rated $\pm 15$ %), max.	0.3 %
Dynamic load smoothing (Iout: 10/90/10 %), Uout $\pm$ typ.	2 %
Load step setting time 10 to 90%, typ.	0.4 ms
Load step setting time 90 to 10%, typ.	0.4 ms
<b>Protection and monitoring</b>	
Output overvoltage protection	< 33 V
Current limitation, typ.	5.25 A
property of the output short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
• typical	8 A
Overload/short-circuit indicator	-
<b>Safety</b>	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.4 mA
Degree of protection (EN 60529)	IP20
<b>Approvals</b>	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
certificate of suitability NEC Class 2	No
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	-
<b>EMC</b>	
Emitted interference	EN 55022 Class A
Supply harmonics limitation	-
Noise immunity	EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
• during operation	0 ... 60 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
Connection technology	screw-type terminals

Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded
• Output	+, -: 2 screw terminals each for 0.5 ... 2.5 mm <sup>2</sup>
• Auxiliary	-
width of the enclosure	50 mm
height of the enclosure	125 mm
depth of the enclosure	120 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.5 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	3 076 166 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

