



Figure similar

Spare part SIMATIC S7-200, Digital input EM 221, only for S7-22X CPU, 16 DI, 24 V DC, sinking-sourcing

Input current	
from backplane bus 5 V DC, max.	70 mA
Power loss	
Power loss, typ.	3 W
Digital inputs	
Number of digital inputs	16
Source/sink input	Yes
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
- Type of input voltage - Rated value (DC) - for signal "0" - for signal "1"	DC 24 V 0 to 5 V +15 to +30 V
Input current	
for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	4.5 ms
Cable length	
- shielded, max. - unshielded, max.	500 m 300 m
Encoder	
Connectable encoders	
2-wire sensor — permissible quiescent current (2-wire sensor), max.	Yes 1 mA
Potential separation	
Potential separation digital inputs	
- Potential separation digital inputs - between the channels, in groups of	Yes; Optocoupler 4
Isolation	
Isolation tested with	500V AC for 1 minute
Connection method	
Plug-in I/O terminals	Yes
Dimensions	

Width	71.2 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	160 g
last modified:	3/12/2021 