



Through-type terminal thermoplast Screw terminal on both sides Single terminal 10 mm, Sz. 16

Model	
product brand name	SETRON
product designation	ALPHA FIX terminal blocks
design of terminal / terminal levels internally linked	No
General technical data	
terminal contact spacing	10 mm
operating voltage / rated value	800 V
Protection class	
combustibility class acc. to UL 94	V2
Main circuit	
operational current / rated value	76 A
Appearance	
color	beige
Product details	
product component / required / end cover plate	No
Number	
number of terminal levels	1
number of terminal points / per terminal level	2
Connections	
stripped length	13 mm
connectable conductor cross-section / solid	
• minimum	1.5 mm ²
• maximum	16 mm ²
connectable conductor cross-section / stranded	
• minimum	2.5 mm ²
• maximum	16 mm ²
connectable conductor cross-section / finely stranded	
• with core end processing / minimum	1 mm ²
• with core end processing / maximum	16 mm ²
• without core end processing / minimum	2.5 mm ²
• without core end processing / maximum	16 mm ²
tightening torque / with screw-type terminals	
• minimum	1.2 N·m
• maximum	1.2 N·m
type of electrical connection	
• 1	screw-type terminal
• 2	screw-type terminal
position / of the terminal	lateral

Mechanical Design	
height / with lowest-profile installation	26 mm
length	41 mm
fastening method	DIN rail 35 mm
net weight	23.3 g
material / of the insulating body	Thermoplast

Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



EG-Konf.

other

Further information

