

Control Power Transformer, 150va, PRI 240x480v, SEC 120x240v, Domestic,	
product brand name	Control Power Transformer
design of the product	Control power voltage
special product feature	Robust design
<b>General technical data</b>	
weight [lb]	6.7 lb
Height x Width x Depth [in]	3.42 × 3.75 × 4.36 in
• ambient temperature [°F] during operation	-4 ... +104 °F
• ambient temperature during operation	-20 ... +40 °C
country of origin	Mexico
operating apparent power rated value	150 V·A
<b>Enclosure</b>	
design of the housing	Open
<b>Mounting/wiring</b>	
mounting position	Any
fastening method	Surface mounting
type of electrical connection at output for main current circuit	Screw-type terminals (touchsafe)
type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)
<b>Inputs/ Outputs</b>	
input variables of primary voltage	240x480vac
output dimensions of secondary voltage	120x240vac
phase number of the inputs	1
electrical input frequency	50 ... 60 Hz
input voltage _1	240 V
input voltage _2	480 V
phase number of the outputs	1
electrical output frequency	60 ... 50 Hz
output voltage _1 rated value	120 V
output voltage _2 rated value	240 V
certificate of suitability	UL / CSA
<b>Further information</b>	

last modified:

5/29/2020 