



Figure similar

Control Power Transformer, 500va, PRI 208/277v, SEC 120v, Domestic,

product brand name	Control Power Transformer
design of the product	Control power voltage
special product feature	Robust design
<b>General technical data</b>	
weight [lb]	19.2 lb
Height x Width x Depth [in]	5.69 × 5.25 × 5.42 in
<ul style="list-style-type: none"> <li>ambient temperature [°F] during operation</li> </ul>	-4 ... +104 °F
<ul style="list-style-type: none"> <li>ambient temperature during operation</li> </ul>	-20 ... +40 °C
country of origin	Mexico
operating apparent power rated value	500 V·A
<b>Enclosure</b>	
design of the housing	Open
<b>Mounting/wiring</b>	
mounting position	Any
fastening method	Surface mounting
type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)
<b>Inputs/ Outputs</b>	
input variables of primary voltage	208/277vac
output dimensions of secondary voltage	120vac
design of fuse holder of the secondary section	Require touchsafe cover
phase number of the inputs	1
electrical input frequency	50 ... 60 Hz
input voltage _1	208 V
input voltage _2	277 V
phase number of the outputs	1
electrical output frequency	60 ... 50 Hz
output voltage _1 rated value	120 V
certificate of suitability	UL / CSA
<b>Further information</b>	

last modified:

3/23/2020 