



Data

Electrical data

Approvals per UL 1059

Rated voltage UL (Use Group B)	300 V
Rated current UL (Use Group B)	20 A
Rated voltage UL (Use Group C)	300 V
Rated current UL (Use Group C)	20 A
Rated voltage UL (Use Group D)	600 V
Rated current UL (Use Group D)	5 A

Geometrical Data

Width	0,8 mm / 0.031 inch
Height	51,7 mm / 2.035 inch

Subject to changes. Please also observe the further product documentation!



Depth	69,7 mm / 2.744 inch
-------	----------------------

Material Data

Color	gray
Fire load	0.072 MJ
Weight	2.4 g

Commercial data

Product Group	22 (TOPJOB S)
Packaging type	BOX
Country of origin	CN
GTIN	4044918691161
Customs tariff number	85389099990

Approvals / Certificates

Ex-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	IECEX Physikalisch Technische Bundesanstalt	IEC 60079	IECEX PTB 03.0004U (Ex eb IIC Gb or Ex eb I Mb)

Downloads

CAD/CAE-Data

CAD data

2D/3D Models 2002-2291

CAE data

EPLAN Data Portal 2002-2291

WSCAD Universe 2002-2291

ZUKEN Portal 2002-2291

Subject to changes. Please also observe the further product documentation!



Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!
