

Data sheet | Item number: 2002-2292
End and intermediate plate; 0.8 mm thick; orange



Data
Electrical data

Approvals per UL 1059

Rated voltage UL (Use Group B)	300 V
Rated current UL (Use Group B)	20 A
Rated voltage UL (Use Group C)	300 V
Rated current UL (Use Group C)	20 A
Rated voltage UL (Use Group D)	600 V
Rated current UL (Use Group D)	5 A
Approvals per	UL 1059

Geometrical Data

Width	0.8 mm / 0.031 inch
-------	---------------------

Subject to changes. Please also observe the further product documentation!



Height	51.7 mm / 2.035 inch
Depth	69.7 mm / 2.744 inch

Material Data

Color	orange
Fire load	0.072 MJ
Weight	2.4 g

Commercial data

Product Group	22 (TOPJOB S)
Packaging type	BOX
Country of origin	CN
GTIN	4044918691154
Customs Tariff No.	85389099990

Approvals / Certificates

Ex-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	IECEx Physikalisch Technische Bundesanstalt	IEC 60079	IECEx PTB 03.0004U (Ex eb IIC Gb or Ex eb I Mb)

Counterpart

Downloads

Documentation

Additional Information

Technical explanations

Apr 3, 2019

CAD/CAE-Data

CAD data

2D/3D Models 2002-2292

Subject to changes. Please also observe the further product documentation!



CAE data

EPLAN Data Portal 2002-2292

WSCAD Universe 2002-2292

Installation Notes

Product family

TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!