



## Data Electrical data

# Ratings per IEC/EN 60664-1

Nominal voltage (III/3)	800 V
Rated surge voltage (III/3)	8 kV

#### **Geometrical Data**

Width	29 mm / 1.142 inch
Height	19 mm / 0.748 inch

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 



Depth	4,1 mm / 0.161 inch	
Material Data		
Color	light gray	
Fire load	0.019 MJ	
Weight	3 g	
Commercial data		
Packaging type	bag	
Country of origin	DE	
GTIN	4055143700252	

85366990990

# Downloads CAD/CAE-Data

Customs tariff number

**CAD** data

2D/3D Models 2004-405/011-000

CAE data

EPLAN Data Portal 2004-405/011-000

WSCAD Universe 2004-405/011-000


ZUKEN Portal 2004-405/011-000

#### **Installation Notes**

Commoning

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 





This star point jumper has been specially developed to create a "star point" and is used on motor terminal boards equipped with TOPJOB® S rail-mount terminal blocks.

### **Product family**

#### TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

Show all products from the family

Subject to changes. Please also observe the further product documentation!