


Data sheet | Item number: 281-407

Test plug; 6 mm wide; Nominal current 24 A; for 0.08 mm² - 2.5 mm²; 2,50 mm²; gray



Subject to changes. Please also observe the further product documentation!



Subject to changes. Please also observe the further product documentation!



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated current	24 A
---------------	------

Connection data

Connection technology	CAGE CLAMP®
Solid conductor	0.08 ... 2.5 mm² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 14 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inch
Total number of connection points	1
Total number of potentials	1
Wiring type	Front-entry wiring

Geometrical Data

Width	6 mm / 0.236 inch
-------	-------------------

Material Data

Color	gray
Fire load	0.032 MJ
Weight	2.2 g

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
Packaging type	BOX
Country of origin	DE
GTIN	4044918255622
Customs tariff number	85366990990

Subject to changes. Please also observe the further product documentation!



Downloads

Documentation

Bid Text

281-407

doc - Datei

281-407

GAEB X81 - Datei

Additional Information

Technical explanations

CAD/CAE-Data

CAD data

2D/3D Models 281-407

CAE data

WSCAD Universe 281-407

ZUKEN Portal 281-407

Installation Notes

Testing

Subject to changes. Please also observe the further product documentation!



Testing with a test plug

(picture shows a test plug fitted with CAGE CLAMP®).

Subject to changes. Please also observe the further product documentation!
