

Data sheet | Item number: 870-402

Push-in type jumper bar; insulated; 2-way; Nominal current 18 A; light gray



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated current	18 A
---------------	------

Subject to changes. Please also observe the further product documentation!

Approvals Ex

Rated current (Ex e II)	13.5 A
-------------------------	--------

Geometrical Data

Width	9 mm / 0.354 inch
Depth	2,5 mm / 0.098 inch

Material Data

Color	light gray
Fire load	0.011 MJ
Weight	0.8 g

Commercial data

Product Group	16 (Rail Mounted Terminal Block with CCC)
Packaging type	BOX
Country of origin	DE
GTIN	4044918506458
Customs tariff number	85366990990

Counterpart

Downloads

Documentation

Additional Information

Technical explanations	Apr 3, 2019
------------------------	-------------

CAD/CAE-Data

CAD data

2D/3D Models 870-402

CAE data

WSCAD Universe 870-402

Subject to changes. Please also observe the further product documentation!

Installation Notes

Jumpered



Commoning with push-in type jumper bars:

Two parallel jumper slots are accommodated in one terminal block.

Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side, until installed.

Push-in type jumper bars 1 – 3 – 5 – 7 or
1 – – 4 – – 7

upon request

Subject to changes. Please also observe the further product documentation!