

Data sheet | Item number: 870-410
Push-in type jumper bar; insulated; 10-way; Nominal current 18 A; light gray



Data
Electrical data

IEC Approvals

Rated current	18 A
---------------	------

Ex information

Rated current (Ex e II)	13.5 A
-------------------------	--------

Physical data

Width	49 mm / 1.929 inch
Height	2.5 mm / 0.098 inch

Material data

Color	light gray
Fire load	0.047 MJ
Weight	4.6 g

Subject to changes. Please also observe the further product documentation!



Commercial data

PU (SPU)	50 (25) Stück
Packaging type	box
GTIN	4044918508537

Downloads

Documentation

Bid Text

870-410	Jan 4, 2018	doc
doc - Datei		24.1 kB

870-410	Feb 19, 2019	xml
X81 - Datei		2.6 kB

Additional Information

Technical explanations	Apr 3, 2019	pdf
		2.2 MB

CAD files

CAD data

2D/3D Models 870-410

CAE data

WSCAD Universe 870-410

ZUKEN Portal 870-410

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 870-410

Push-in type jumper bar; insulated; 10-way; Nominal current 18 A

Installation Notes

Subject to changes. Please also observe the further product documentation!

Commoning



Commoning with push-in type jumper bars:

Two parallel jumper slots are accommodated in one terminal block.



Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side until installed.

Push-in type jumper bars 1 – 3 – 5 – 7 or
1 – – 4 – – 7

upon request

Subject to changes. Please also observe the further product documentation!